


UNSTABLE RESONATOR SEMICONDUCTOR LASERS

**Andrew P. Ongstad, Ron Kaspi (AFRL)
Gregory Dente (GCD Associates)
Michael Tilton, Joseph Chavez, Donald Gianardi, Jr. (Boeing LTS)**

25 October 2005

Conference Paper

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED.



**AIR FORCE RESEARCH LABORATORY
Directed Energy Directorate
3550 Aberdeen Ave SE
AIR FORCE MATERIEL COMMAND
KIRTLAND AIR FORCE BASE, NM 87117-5776**

REPORT DOCUMENTATION PAGE				<i>Form Approved</i> OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.					
1. REPORT DATE (DD-MM-YYYY) 25-October-2005		2. REPORT TYPE Conference Paper Preprint		3. DATES COVERED (From - To) 01-August-2004 - 7-Jul-2005	
4. TITLE AND SUBTITLE Unstable Resonator Semiconductor Lasers				5a. CONTRACT NUMBER N/A - In-House (DF297213)	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER 63605F	
				5d. PROJECT NUMBER 4866	
6. AUTHOR(S) Andrew P. Ongstad, Ron Kaspi (AFRL) Gregory Dente (GCD Associates) Michael Tilton, Joseph Chavez, Donald Gianardi, Jr. (Boeing LTS)				5e. TASK NUMBER LY	
				5f. WORK UNIT NUMBER 12	
				8. PERFORMING ORGANIZATION REPORT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) AFRL/DELS 3550 Aberdeen Avenue SE Kirtland AFB NM 87117-5776				10. SPONSOR/MONITOR'S ACRONYM(S)	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) Air Force Research Laboratory 3550 Aberdeen Avenue SE Kirtland AFB NM 87117-5776				11. SPONSOR/MONITOR'S REPORT NUMBER(S) AFRL-DE-PS-TP-2006-1001	
12. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.					
13. SUPPLEMENTARY NOTES Presentation for MIOMD-VII Conference in Lancaster, England, 12 September 2005. GOVERNMENT PURPOSE RIGHTS: The U.S. Government has the right to use, modify, reproduce, release, perform, display, or disclose the work to authorize others to do so for U.S. Government purposes only.					
14. ABSTRACT We describe high-brightness, broad-area mid-IR semiconductor lasers. The optically pumped devices achieved higher brightness operation as unstable resonators. Each unstable resonator was realized by polishing or etching a diverging cylindrical mirror at one of the facets. In general, for facet separation L and diverging facet mirror radius R, the geometry generates two virtual mode source points located at distances $V = \pm \sqrt{L^2 + LR}$ from the flat facet. Radiation from a virtual source point is characterized by reimagining onto itself after a round trip through the resonator. If we refer to the figure, the left virtual source, $V(+)$, is at an object distance ($V+L$) from the diverging mirror with focal length ($-R/2$). Upon reflection from the curved facet, the radiation forms a virtual image, $V(-)$, at a distance ($V-L$) to the right of the curved facet. These distances satisfy the imaging equation $\frac{1}{V+L} - \frac{1}{V-L} = -\frac{2}{R}.$ This regenerative reimagining of the circulating radiation is the critical mechanism leading to high brightness from the virtual source locations. In actual operation, we outcouple the radiation from the flat facet side of the device, so that the virtual waist of the lateral mode is located behind the output facet at a refractively reduced distance, $D = V/n$, in which the index of refraction is given by $n=3.82$. For a typical device geometry with $L = 2500$ mm and $R = 10000$ mm, this reduced distance is inside the device at approximately 1460 mm from the flat facet. In addition to the high brightness generated by the regenerative reimagining of the virtual source points, the natural divergence of the propagating mode tends to mitigate self-focusing filamentation, leading to further brightness improvements. For several mid-IR unstable resonator devices, we will show experimental near- and far-fields near threshold, as well as at many times threshold. For these devices, the far-field is realized by reimagining the high-brightness virtual source point located a distance D from the flat facet.					
15. SUBJECT TERMS Optically pumped semiconductor lasers, antimonides, W lasers, mid-IR semiconductor lasers, unstable resonators					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Unlimited	18. NUMBER OF PAGES 19	19a. NAME OF RESPONSIBLE PERSON Dr. Andrew Ongstad
a. REPORT Unclassified	b. ABSTRACT Unclassified	c. THIS PAGE Unclassified			19b. TELEPHONE NUMBER (include area code) (505) 853-3207

Unstable Resonator Semiconductor Lasers

Gregory Dente
(GCD Associates)

Michael Tilton, Joseph Chavez, Donald Gianardi Jr.
(Boeing LTS)

Andrew Ongstad, Ron Kaspi
(AFRL/DELS)

Opening intro chart

**SLIDES ONLY
NO SCRIPT PROVIDED**

**CLEARED
For Open Publication**

This is a
SAF/PAX document

SEP 20 2005 5

05-0389

Office of Security Review
Department of Defense

Call 697-0422 or 697-6715
For pickup or return to
4A120

AFRL/DE 05-299


15-5-1981

Outline


- I.** Introduction
 - Mode Control in High-Power Semiconductor Lasers
 - Mode-Media Interactions (Filament Formation)
- II.** Suppressing Filaments
- III.** Unstable Resonators for semiconductor lasers.
- IV.** Summary & Outlook

We will read the chart, we will offer some of the history of filament formation.


I. Introduction - Mode Control in High Power SL's



- Narrow stripe gives good BQ but low power ($10-20 \text{ mW}/\mu\text{m}$ of stripe)





- Wide stripe gives poor BQ but high power; mode break-up with filament formation occurs



This chart describes the mechanisms of mode-media interaction in broad-area semiconductor lasers.

Gain / Index in Semiconductor Lasers

- *Band to Band transition:*




- *Saturable index at gain peak creates self-focusing*

This chart shows the asymmetric gain versus frequency curve for a typical band-to-band transition. This asymmetry leads to saturable index of refraction at the gain peak, the origin of self-focusing.


II. The Tilted Amplifier Solution

- *Several research groups have observed that tilted amplifiers can provide high-gain as well as good BQ:*




We will discuss the experiments on tilted semiconductor amplifiers that were done between 1990 -1995.

**600 μm x 1500 μm Amplifier Results
7° angle of incidence (air)**



This chart shows the configuration for a TWA, that provided 21 Watts of diffraction limited output power in a 1992 experiment.



These are the published results from that experiment.

Beam Propagation Method

*Paraxial wave equation in the diode with filamentation
tendencies given by α -parameter*

$$\frac{1}{2ik} \frac{\partial^2 U}{\partial x^2} + \frac{\partial U}{\partial z} = \frac{\Gamma G(N(x,z))}{2} \cdot (1 - i\alpha) \cdot U$$


(α – linewidth enhancement factor)

$$U(x,z) = F(x,z) \quad \text{or} \quad B(x,z)$$


Carrier diffusion in the diode

$$D_e \frac{\partial^2 N}{\partial x^2} - \frac{N}{\tau_s} - \frac{G}{h\nu} \cdot (I_f + I_b) + \frac{\eta J}{qW_a} = 0$$


Wave optics modeling of semiconductor lasers or amplifiers requires simultaneous self-consistent solutions of the wave equation and the carrier diffusion equation.



This figure shows our modeling geometry.




These are our simulation results, showing excellent agreement with the 1992 experiment.



This chart illuminates the substantial benefits realized by angled extraction.

Ways to avoid counterpropagation and achieve angled extraction without filamentation




- *We will now concentrate on unstable resonators.*

All of these resonator configurations essentially avoid exact counterpropagation and offer promise for high power and good beam quality.

III. Unstable Resonators

- Invented by A. Siegman




- Large mode volumes
- Near diffraction limited performance (good mode discrimination)
- Insensitive to misalignments and aberrations in the medium
- Avoids exact counterpropagation and suppresses filaments

- Applications to semiconductor lasers


- Bogatov, et.al. (1980) - polished facet mirror
- Craig, PhD Dissertation (1985) - etched facet mirrors
- Yariv, Salzman, et.al. (1985-87) - etched facet mirrors
- Tilton, Dente, et.al. (1989-present) - ion milled, etched, lens train

The unstable resonator has a long history and we will essentially cover that here.



These are the types of unstable resonators that have been implemented on semiconductor lasers.

High-Brightness from an Unstable Resonator Mid-IR Semiconductor Laser



- Two virtual mode source points located at distances $V = \pm \sqrt{L^2 + LR}$ from the flat facet; $L = 3.4$ mm, $R = 7.5$ mm, $V/n = 1.6$ mm.
- The left virtual source, V_+ , is at an object distance $(V+L)$ from the diverging mirror with focal length $(-R/2)$. Upon reflection from the curved facet, the radiation forms a virtual image, V_- , at a distance $(V-L)$ to the right of the curved facet. These distances satisfy the imaging equation:

$$\frac{1}{V+L} - \frac{1}{V-L} = -\frac{2}{R}$$


This chart illustrates the unstable resonator that we used in our recent experiment on optically pumped mid-ir semiconductor lasers.

We will read through this chart.

Improving lateral beam quality

On-chip unstable resonator with etched curved back facet.


Preliminary qualitative measurements show greatly improved lateral coherence




This chart shows the farfields of both a Fabry-Perot resonator and our unstable resonator. The right hand pictures show farfield interference when a double slit is inserted into the near field.

IV. Conclusions

- *Filament formation problems have precluded high-power, good BQ, operation of broad-area semiconductor laser devices.*



- *Off-axis extraction, with angled counter-propagating fields, is an excellent way to ameliorate the filamentation tendencies.*



This final chart reviews the essential physics of mode-media interaction and filament formation, in addition it recalls the basic methods for obtaining high power and suppressing filaments.